

DESIGN INTERFACE MANAGEMENT SYSTEM (DIMS) FOR CONSTRUCTION PROJECTS

V. Senthilkumar¹, Koshy Varghese²

¹Research scholar, BTCM Division, IIT Madras India

²Professor, BTCM Division, IIT Madras India

Keywords: diMs, Interface Management, Physical Interface Matrix, Design Interface Matrix

1 INTRODUCTION

The complex information intensive and dynamic nature of the fast track / concurrent construction design process makes it hard to manage the information flows using the traditional project management techniques and tools. Since the concurrent project execution advocates the Engineering Procurement and Construction (EPC) firm to start all its processes in parallel, design parameters involved in the process are dynamic in nature. The failure to anticipate the impact of the change of these design parameters generally affects the design quality, and causes design revisions, delay etc. Conventional design management procedures are partially successful in getting the designer's involvement because it is time intensive and designers are not sure if it will be useful. Moreover, the designers fail to anticipate all the probable design interfaces at the initial stage.

This paper proposes a new methodology 'DIMS' for managing dynamic design information in the detailed design phase. It has five main components, (i) Identification/Definition of project elements, (ii) Development of the Physical Interface Matrix (PIM): capturing the physical interfaces among the components, (iii) Development of Design Interface Matrix (DIM): capturing the design interfaces between the components and the disciplines, (iv) Development of Design Interface Agreement (DIA): capturing the detailed design interface parameters, (v) Developing Drawing DSM: capturing the design interfaces between the drawings and its Optimization to ensure optimal drawing release sequences. This methodology is demonstrated through implementation on an industrial design project.

2 DSM METHODOLOGY

The DSM methodology has been applied in various design domains including construction (Rogers and Salas, 1999; Eppinger et al., 1994; Tang et al., 2000, Austin et al. 1996). The utilization of DSM based tool in real world projects is constrained by its size and factors such as distributed work culture, expert time etc(Senthilkumar and Varghese, 2008) . Although extensive DSM research has been carried out in activity sequencing and iteration modelling for all levels of the design process, little work has been done in formulating the DSM and capturing the interfaces at various levels of the construction design process (Eppinger et al., 2008). The objective of this work is to: (i) Propose a structured methodology to decompose and integrate the project at appropriate levels to minimize the size of the DSM (ii) Evolve a methodology to capture the design interfaces with minimum effort from the designers and utilizing distributed work culture concepts and (iii) Generate drawing vs drawing interfaces and manage the interfaces for design optimization.


3 DIMS METHODOLOGY

Figure 1 shows the DIMS methodology and various steps involved in it, the methodology is shown in the left column.

In Entity-Identification stage, the project is decomposed into various levels as shown in Step 1 of figure 1. Various levels identified are systems, main components, subcomponents, disciplines and parameters.

In Interface-Identification stage, all parties involved are required to identify their interfaces with others parties through workshop or brainstorming session. In the detailed design stage, the design interfaces exist only when a component/ subcomponent has the physical interface with the other component /subcomponent. Hence the physical interfaces are captured for the top level elements in the hierarchy.

Figure 1 DIMS Model



The physical interfaces between the subcomponents/components are captured using the Physical Interface Matrix (PIM). Step 2 in figure 1 shows an example PIM of the Factory Region of a Glass Factory design.

From PIM, the components which have physical interfaces are grouped for capturing the design interfaces in the next step through Design Interface Matrix (DIM).

The DIM captures the design information interfaces between the physically interfaced components and the design disciplines involved. Step 3 in figure 1 shows an example DIM for a Batching Plant main component. The yellow region represents the general design interfaces between the disciplines apart from their subcomponent specific design interfaces. One cannot list out all the sub components which are present in main component. The missed out subcomponent's design interfaces can be captured through the first yellow region. The design interfaces are captured by populating the DIM through brainstorming, expert opinion or workshop. Then the same is updated in the subsequent meetings.

Next, each discipline enters the detailed interfacing issues in the form of Design Interface Agreement (DIA) as shown in step 4 of figure 1. In the illustration, the 'X' mark between 'Struct' and 'Lift' in the DIM is taken and the issues details related to the same are recorded in the DIA.

The final step is to identify the drawing and issues relationships through the framework presented in step 5 of figure 1. Based on this framework the drawing DSM is developed.

4 AUTOMATED TOOL 'diMs'

It is very difficult to implement the above methodology by the manual methods as it is tedious to maintain the documents and the matrices. Also the parties involved in the construction design process are distributed geographically which again makes the information flow complex and time consuming. A server based automated prototype tool using the above methodology called 'diMs' is developed to facilitate management of distributed concurrent design. The features of the tool will be further explained with the case study in the presentation.

5 SUMMARY

The DIMS methodology gives guidelines to the construction designer manager for decomposing and integrating the project design. The drawing DSM is developed through PIM DIM and DIA. These drawing dependencies are used for making decision in the drawing execution sequence. Also it is giving guidance to the designers to identify the affected parties because of the changes made in their drawings by the updated design information. The dynamic nature of this drawing DSM will also reduce the complexity in the interfaces as the design progresses.

REFERENCES

- [1] Austin, S, Baldwin, A, and Newton, A. 1996, 'A Data Flow Model to Plan and Manage the Building Design Process', *Journal of Engineering Design* Vol. 7. No 1, 1996. p.3 -25.
- [2] Eppinger, S.D, Whitney. D. E, Smith. R. P and Gebala. D. A 1994, 'A Model-based Method for Organizing Tasks in Product Development', *Research in Engineering Design*, 6, p.1-13.
- [3] Rogers, J L and Salas, A O (1999), 'Toward a More Flexible Web-based Framework for Multidisciplinary Design', *Advances in Engineering Software*, Vol 30, p. 439 – 444.
- [4] Tang, D, Zheng, L, Li, Z, Li, D and Zhang, S (2000), 'Re-Engineering of the Design Process for Concurrent Engineering', *Computers and Industrial Engineering*, Vol 38, p. 479-491.
- [5] Senthilkumar. V and Varghese, K (2008), 'Workflow and Organizational Structuring of Design Projects; Analysis of Two Case Studies in India', *Joint Conference & Workshop Design Management in the AEC Sector*, University of São Paulo, Brazil, 4-8 November 2008.
- [6] Eppinger, S.D, Whitney. D. E, and A.A. Yassine (2008), 'The Design Structure Matrix – DSM Homepage, <http://www.dsmweb.org/> Last visited 31/08/2008.

Contact: V. Senthilkumar
Indian Institute of Technology
BTCM Division, Civil Engineering Department,
600036, Chennai, Tamilnadu, India
Phone: +91 44 22575255. Fax: +91 44 22574252
vsenthil@iitm.ac.in



10TH INTERNATIONAL DSM CONFERENCE

DESIGN INTERFACE MANAGEMENT SYSTEM (diMs) FOR CONSTRUCTION PROJECTS

V. Senthilkumar
Koshy Varghese

Indian Institute of Technology Madras, India



Technische Universität München



Index

1. Introduction
2. Limitations of DSM Applications in Construction Projects
3. Objectives of diMs Methodology
4. diMs Methodology
5. Application Example
6. diMs – Prototype
7. Summary



Technische Universität München





Introduction

- Design - Driven by Information Exchanges
- Conventional Design – Sequential Execution
- Concurrent/ Fast Track Techniques – Parallel Execution
- Multidisciplinary Design – Interface Management
- Assumptions – Essential to Validate



Challenges of DSM Applications in Construction Projects

- Interface capturing process - Difficult - Size and structure of the project.
- Foreseeing all the interfaces at the start of the project – Difficult
- Tools - Not effective in assisting the interface identification process.
- More time required to develop the DSM – Designers involvement reduced
- Terminologies – Different - Not construction specific





Objectives of diMs Methodology

- (i) Propose a structured methodology to decompose and integrate the project at appropriate levels to minimize the size of the DSM
- (i) Evolve a methodology to capture the design interfaces with minimum effort from the designers and utilizing distributed work culture concepts
- (ii) Generate drawing vs. drawing interfaces and manage the interfaces for design optimization.



Terminologies

- **System** – Geographically distinct entity, created to meet specific high level functions. A project may consist of many systems.
For example;
 - *Passenger Terminal Building, Airside and landside in Airport Project*
 - *Factories buildings, Admin buildings in Glass factory project.*



Airside

Passenger Terminal Building

Landside





Terminologies

- **Main Component** – Physical entity for which a specific category of drawings are produced. A system consists of many main components.

For example;

- *Each Floors in Passenger Terminal Building System in Airport Project*
- *Batching Plant, Chimney, Furnace etc. in Factories building system on Glass Factories design*



Arrival Level



Departure Level



Restaurants and Shops Level



Terminologies

- **Sub Component** – Also a physical entity which forms a part of the main component.

For example;

- *Lifts, Hand rails, HVAC Ducts, FIDS etc in PTB*
- *Machineries, Ducts, Cranes and other lower level physical entities present in factories*



FIDS



Currency Exchange Kiosk



Lift






Terminologies

- Team** – A Team is a group of people who are working for specific functional requirements of the project.
 For example:
 - Structural, Architecture, Electrical, HVAC, Client, Consultants, Vendors etc.
- Drawing** – A drawing is a lowest physical output of the construction design, - based on the main components also Team specific.
 For example;
 - Basement foundation drawing by Structural engineering Team
 - Electrical cut-outs and wiring layout by Electrical engineering Team
- Parameter** - A parameter is an input, output data in the design process. A drawing consists of many parameters.
 For example;
 - Depth of footing, cut-outs size
 - Sizes of reinforcements etc




Relationship Diagram






diMs Methodology



Entities - Identification





Interface - Identification Physical Interface Matrix (PIM)

Sub Components	Main Component			
	Main Component 1	Main Component 2	Main Component 3	Main Component 4
Sub Component 1	x		x	
Sub Component 2		x	x	
Sub Component 3	x		x	x
Sub Component 4	x	x		
Sub Component 5		x	x	x
Sub Component 6	x		x	
Sub Component 7	x			x




Interface - Identification Design Interface Matrix (DIM)

Gives information to	Gets information from			
	Team 1	Team 2	Team 3	Team 4
Team 1			x	
Team 2	x	x		
Team 3		x		
Team 4			x	
Sub Component 1		x		
Sub Component 3				x
Sub Component 4	x	x		x
Sub Component 6		x		
Sub Component 7			x	






Manage Interfaces – Drawing DSM Formation Framework



Entities – Identification (Glass Factory Project)





Physical Interface Matrix (PIM) – (Factories System)

	Electrical	Control	Hydraulic	Pneumatic	Mechanical	Thermal
Electrical	X					
Control	X	X				
Hydraulic			X			
Pneumatic			X	X		
Mechanical					X	
Thermal						X
Conveyors	X					
Equipment	X	X	X	X	X	X
Electrical	X	X	X	X	X	X
Trucks	X	X	X	X	X	X
Grain Elevator	X		X			
Cell Elevator	X					X
Loading Bay	X					X
Crane Lining		X	X			
Rolling Mills	X		X	X	X	X
Formers	X		X	X	X	X
Hand Lifting	X	X	X	X		
Grade Grab M/GF	X			X	X	X
Fluid Tanks	X		X	X	X	X
CE	X	X	X	X	X	X
Cell Elevator	X		X	X	X	X



Design Interface Matrix (DIM) – (Batching Plant Component)

Gets Information From	Control	Signal	Information	Control	Signal	Fire Fighting
Control	X					
Signal	X	X				
Information			X			
Control			X	X		
Signal	X			X		
Fire Fighting					X	X
Electrical		X				X
Hydraulic		X				
Equipment	X	X		X		X
Electrical	X	X		X		X
Fire Fighting					X	X
Control						X
Conveyors					X	X
Equipment	X	X		X		X
Electrical	X	X		X		X
Trucks			X		X	
Grain Elevator					X	X



Design Interface Agreement (DIA)

Design Interface Agreement (Sample Only)
E. 4. 4

Interfacing Between Department (S) and Department (M)		DIA Type 4	Batching Plant
Parent Department: Structures		Interfacing Department: Mechanical	
Sl. No.	Interfacing Issues	Agreed Commitments/ Constraints	Status of Issue
1	Latency of drawings	Availability of 2D files to be provided by the parent department by 12 May 07	Open
2	Latency of drawings	Availability of 2D files of the parent department	Open
3	Clearance for LAT drawing within	2D files to be provided by parent department	Open
4	Latency of 3D file upload	3D files to be provided by parent department by 12 May 07	Open
5	Required for visible section details drawings	3D files to be provided by parent department by 12 May 07	Open
6	Dimensional drawings to be required	3D files to be provided by parent department by 12 May 07	Open
Signature of Parent Department		Signature of Interfacing Department	



Technische Universität München



10th International DSM Conference 2008- 19



About "diMs"

- Server based Proto-type
- Developed using PHP and MySql
- Data are stored in DB tables
- Integrity and dynamic nature of the table is maintained by relating the DB tables



Design Interface Management System

"Weaves Interfaces"





User Name

Password



Technische Universität München



10th International DSM Conference 2008- 20



Summary

- Gives guidelines to the construction design manager for decomposing and integrating the project design.
- PIM, DIM captures the Physical and design Interfaces
- Drawing DSM is developed through PIM DIM and DIA.
- Drawing dependencies are used for making decision in the drawing execution sequence.
- Gives guidance to the designers to identify the affected parties because of the changes made in drawings by the updated design information.
- Dynamic drawing DSM reduces the complexity in the interfaces as the design progresses.
- Scope for utilizing the PIM for construction Interface needs to be further examined

